


TISVA®

FEEL THE WARMTH. SEE THE LIGHT.

New Architectural Product
Launch

(COB / Utility Panel)



The Flow:

✓ Propositions of Innovative COB Series :

Product Image, Consumer benefits , MRP , Technical Specifications , Reference Application Image

✓ Propositions of New Panel :

Product Image, Consumer benefits , MRP , Technical Specifications , Reference Application Image

LINOS: Focused (Narrow Beam) COB

Focus Fixed COB : “ LINOS”



MRP: INR 899/-

Consumer Benefits

- **Low Glare** : Deeply embedded LEDs reduces discomfort caused by direct light entering the eye.
- **Longer Lifetime**: High Grade **OSRAM LED CHIP** offers $\geq 30,000$ luminaire lifetime.
- **Durable** : Die Cast Aluminum body makes it a **sturdy** and **long-lasting** product.
- **Certified Quality** : **BIS certified driver** and **LM80 certified LED chip** speaks for the high product quality and class.
- **Better Accentuation of Artifacts and Spaces** with Narrow Beam Angle

Focus Fixed COB : “ LINOS”

Technical specifications

Catalogue No.	DL320905
SAP Code :	8159320905
Wattage	3W
CCT(K)	3000
SDCM	<4
Rated Luminous Flux	185
CRI	>80
Beam	16 degree
Housing	Die Cast Aluminium powder coated in matt white
Driver O/p Voltage	2-5 V DC
Driver O/p Current	600mA
THD	<20%
Surge	≥ 2.5 kV
Power Factor (@ Vin 230V)	0.567
Operating Voltage	90-264V
Lifetime of Luminaire	≥30khrs
Dimension (D x H mm)	Ø42*49 mm
Cutout (D mm)	Ø38 mm
IP Protection	20
Dimming application	NO
Average Weight(g)	87g

Refer manuals for detailed installation instructions .
(Ctrl+ Double Click on icon)



Reference Application Image



Applications: Residential/ Retails/ Hospitality

JENO: Flexible Directional Lighting COB

TISVA®

FEEL THE WARMTH. SEE THE LIGHT.

Focus COB : "JENO"

RECESSED SQUARE 7.5 W



MRP: INR 2 999/-

RECESSED ROUND 7.5 W



MRP: INR 2 799/-

Consumer Benefits

- **Multi Purpose Luminaire** : Inside Out LED directional COB can adjusted 90° vertically and 180° horizontally.
- **Longer Lifetime**: High Grade **CREE LED CHIP** offers ≥ 30,000 luminaire lifetime.
- **Durable** : Sturdy Die Cast Aluminum body .
- **Certified Quality** : **BIS certified driver** and **LM80 certified LED chip** speaks for the high product quality and class.
- **Family of Fixtures**: Comes with a complete range with Round and Square rings to match the vibe of the space.

Refer manuals for detailed installation instructions
(Ctrl+ Double Click on icon)



Technical specifications

Catalogue No.	DL820904	DL820905
SAP Code :	8159820904	8159820905
Wattage	7.5W	7.5W
CCT(K)	3000	3000
SDCM	≤4	≤4
Rated Luminous Flux	450	450
CRI	>80	>80
Beam	24 degree	24 degree
Housing	Die Cast Aluminium powder coated in black and grey	
Driver O/p Voltage	25-45 V DC	25-45 V DC
Driver O/p Current	150mA	150mA
THD		
Surge	≥ 2.5 kV	≥ 2.5 kV
Power Factor (@ Vin 230V)	0.9	0.9
Operating Voltage	165-265V	165-265V
Lifetime of Luminaire	≥30khrs	≥30khrs
Dimension	Ø72*128 mm	75*75*131 mm
Cutout	Ø65 mm	65*65 mm
IP Protection	20	20
Dimming application	NO	NO
Average Weight(g)	480g	520g

Reference Application Image



Applications: Museums/ Retails/ Residences / Hospitality / Offices

VITO: Deep Recessed Panel

Deep Recessed Panel: “ VITO ”



7.5 W : MRP: INR 1 249/-
13 W : MRP: INR 1 599/-

Consumer Benefits

- **Anti Glare : Deep Recessed and High efficiency diffuser** delivers excellent illumination with high eye comfort.
- **Aesthetically Appealing :** The deep recessed white diffuser gives it a clean ceiling look thereby concealing the actual source of light.
- **Durable :** Die Cast Aluminum body makes it a **sturdy** and **long-lasting** product.
- **Certified Quality :** **BIS certified driver** and **LM80 certified LED chip** speaks for the high product quality and class.

Refer manuals for detailed installation instructions
(Ctrl+ Double Click on icon)



Technical specifications

Catalogue No.	DLP802241	DLP803241	DLP806241	DLP130241	DLP130341	DLP130641
SAP Code :	8167802241	8167803241	8167806241	8167802411	8167803421	8167806421
Wattage	7.5W			13W		
CCT(K)	3000	4000	6500	3000	4000	6500
SDCM	≤6			≤6		
Rated Luminous Flux	550			950		
CRI	>80			>80		
Beam						
Housing	Die Cast Aluminium powder coated in white			Die Cast Aluminium powder coated in white		
Driver O/p Voltage	24-45 V DC			24-45 V DC		
Driver O/p Current	160mA			300mA		
THD	10%			10%		
Surge	≥ 2.5 kV			≥ 2.5 kV		
Power Factor (@ Vin 230V)	0.9			0.9		
Operating Voltage	100-265V			100-265V		
Lifetime of Luminaire	≥30khrs			≥30khrs		
Dimension	Ø78*55 mm			Ø103*58 mm		
Cutout	Ø72 mm			Ø98 mm		
IP Protection	20			20		
Dimming application	NO			NO		
Average Weight(g)	136g			200g		

Reference Application Image



RIO-SF: Surface COB

TISVA®

FEEL THE WARMTH. SEE THE LIGHT.

Surface COB: "RIO"



*** FREE ROSE GOLD REFLECTOR WITH PACKAGE**

***FREE CHROME REFLECTOR WITH PACKAGE**

Consumer Benefits

- **Aesthetically Appealing : Choice of Reflectors** gives it an edgy look and a perfectly suitable product to blend in with the space.
- **Durable** : Die Cast Aluminum body makes it a **sturdy** and **long-lasting** product.
- **Certified Quality : BIS certified driver** and **LM80 certified LED chip** speaks for the high product quality and class.

6 W : MRP: INR 1 490/-
12 W : MRP: INR 1 990/-
18 W : MRP: INR 2 590/-



Technical specifications : 6 W

Catalogue No.	DL0610901	DL0611101	DL0630901	DL0631101
SAP Code :	81590610901	81590611101	81590630901	81590631101
CCT(K)	3000	3000	4000	4000K
SDCM	≤3			
Rated Luminous Flux	500			
CRI	>80			
Beam	30 Degree			
Housing	Die cast Aluminium with powder coated in Black	Die cast Aluminium with powder coated in white	Die cast Aluminium with powder coated in Black	Die cast Aluminium with powder coated in white
Driver O/p Voltage	24-45 V DC			
Driver O/p Current	150mA			
THD				
Surge	≥ 2.5 kV			
Power Factor (@ Vin 230V)	0.9			
Operating Voltage	100-265V			
Lifetime of Luminaire	≥30khrs			
Dimension	Ø55*86 mm			
IP Protection	20			
Dimming application	NO			
Average Weight(g)	190g			

Technical specifications : 12 W

Catalogue No.	DL1210901	DL1211102	DL1230901	DL1231102
SAP Code :	81591210901	81591211102	81591230901	81591231102
CCT(K)	3000	3000	4000	4000K
SDCM	≤3			
Rated Luminous Flux	900			
CRI	>80			
Beam	30 Degree			
Housing	Die cast Aluminium with powder coated in Black	Die cast Aluminium with powder coated in white	Die cast Aluminium with powder coated in Black	Die cast Aluminium with powder coated in white
Driver O/p Voltage	24-45 V DC			
Driver O/p Current	300mA			
THD				
Surge	≥ 2.5 kV			
Power Factor (@ Vin 230V)	0.9			
Operating Voltage	100-265V			
Lifetime of Luminaire	≥30khrs			
Dimension	Ø75*110 mm			
IP Protection	20			
Dimming application	NO			
Average Weight(g)	350g			

Technical specifications : 18 W

Catalogue No.	DL1210901	DL1211102	DL1230901	DL1231102
SAP Code :	81591210901	81591211102	81591230901	81591231102
CCT(K)	3000	3000	4000	4000K
SDCM	≤3			
Rated Luminous Flux	1300			
CRI	>80			
Beam	30 Degree			
Housing	Die cast Aluminium with powder coated in Black	Die cast Aluminium with powder coated in white	Die cast Aluminium with powder coated in Black	Die cast Aluminium with powder coated in white
Driver O/p Voltage				
Driver O/p Current				
THD				
Surge	≥ 2.5 kV			
Power Factor (@ Vin 230V)	0.9			
Operating Voltage	100-265V			
Lifetime of Luminaire	≥30khrs			
Dimension	Ø95*130 mm			
IP Protection	20			
Dimming application	NO			
Average Weight(g)	500g			

Reference Application Image




Applications: Museums/ Retails/ Residences / Commercial/Healthcare


TISVA®

FEEL THE WARMTH. SEE THE LIGHT.

RIO ACCESSORY : PENDANT ACCESSORY FOR 12 W



MRP: INR 449/-



MRP: INR 449/-

RIO ACCESSORY : PENDANT ACCESSORY FOR 12 W

Catalogue No.	DL120901	DL121101
SAP Code :	8159120901	8159121101
Housing	Die cast Aluminium with powder coated in Black	Die cast Aluminium with powder coated in white
Dimension	Ø80*1035 mm	
IP Protection	20	
Dimming application	NO	
Average Weight(g)	50g	

Refer manuals for detailed installation instructions
(Ctrl+ Double Click on icon)



PDF
MANUALS

Reference Application Image



Applications: Residences/ Offices / Hospitality / Eating Outlets

Reference Application Image



Applications: Museums/ Retails/ Residences / Commercial/Healthcare

TISVA®

FEEL THE WARMTH. SEE THE LIGHT.

Thank you....

